

KT1085WM Mongoose Raider Quad Technical Bulletin – Assembly



As part of our ongoing commitment to customer satisfaction, we recently updated the assembly manual to include revised instructions for installing the rear axle and handlebar on the Mongoose Raider Quad. Please review all aspects of the User Guide to ensure proper assembly, use and maintenance of the vehicle.

Assembly: Inserting the Rear Axle (page 3)

1. Turn the vehicle body over.
2. Remove the locknut from the axle and remove one #12 washer.
3. Remove one washer from Accessory Pack and slide it onto the axle so that it will be against the body. Note below picture.



4. Slide the rear axle through the hole near the rear of the vehicle body.
5. **IMPORTANT:** The part of the axle with the two washer retainers **MUST** be inserted so that it is positioned on left side of the unit.

Assembly: Inserting the Handlebar (page 7)

1. Insert the handlebar steering column through the opening in the front of the vehicle body
2. Slightly lift the front end of the vehicle body up.
3. Check to ensure the steering column fit through the hole in the steering linkage.
4. Push on the handlebar and snap into place.
5. You now need one washer and one cotter pin from the Accessory Pack.
6. Tip the unit up to view the bottom steering column.
7. Slide on one washer and insert one cotter pin into the small pin hole and use a flat head screwdriver to spread open.

